


## METALLIC

### TRANSLUCENT SURFACES - LUCERE



Texture: 5  
 Lustre: 5  
 Transparency: 3

<b>AVAILABLE DOWNLOADS</b> (click on the link or go to this product's Downloads tab on the website)	<a href="#">Baresque_Lucere_Handling_Fabrication_Installation_Guide.pdf</a> <a href="#">Baresque Cable Systems Guide.pdf</a> <a href="#">Baresque Framing Systems Guide.pdf</a>
<b>DESCRIPTION / FEATURES</b>	Lucere is a poured acrylic resin which is then used to encapsulate various materials providing a sheet with unparalleled depth and clarity
<b>HOW TO SPECIFY</b>	<ol style="list-style-type: none"> <li>1. Design / Colour name</li> <li>2. Sheet size</li> <li>3. Sheet thickness</li> <li>4. Surface finish for each side</li> </ol>
<b>COMPOSITION</b>	Fabric embedded in acrylic
<b>SHEET SIZE</b>	2440mm x 1220mm or 2000mm x 1000mm
<b>THICKNESS</b>	6mm, 8mm or 11mm
<b>SURFACE FINISH</b>	Gloss/Gloss, Matt/Matt or Gloss/Matt
<b>PATTERN REPEAT</b>	N/A
<b>WEIGHT</b>	6mm - 6kg/m <sup>2</sup> , 8mm - 8kg/m <sup>2</sup> , 11mm - 11kg/m <sup>2</sup>
<b>CUSTOMISABLE</b>	Yes. 10 sheet minimum
<b>INDOOR / OUTDOOR</b>	Indoor use only
<b>WET AREAS</b>	Yes. Edges must be sealed
<b>FABRICATION</b>	Standard wood working tools. See Baresque Lucere Handling, Fabrication and Installation guide for more details.
<b>THERMOFORMABLE</b>	Yes



**baresque.com.au**  
 e info@baresque.com.au  
 p 1300 306 399

<b>INSTALLATION</b>	Most glass fittings can be used. See Baresque Lucere Handling, Fabrication and Installation guide for more details.
<b>REFINISHABLE</b>	Fully refinishable to matt or gloss
<b>ADDITIONAL COMMENTS</b>	<p>1. Being handmade, slight imperfections in Lucere are deemed acceptable. These slight imperfections may include small bubbles in the interlayer or slight surface texture imperfections. Any imperfection that is not visible one (1) meter away from the panel is deemed within commercial tolerance.</p> <p>2. Lucere sheets may not be perfectly flat. Due to this, it is always suggested that the sheet be fully framed or mechanically fixed.</p>
<b>LEAD TIME</b>	6 weeks (approx) from Wednesday + 1 week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.
<b>CARE INSTRUCTIONS</b>	<p>* Do not use glass cleaning products, acetone, gasoline, benzene, lacquer thinner, chlorinated solvents, gritty abrasive scouring compounds, or alkaline cleaners to clean Lumicor as damage to the sheet will occur</p> <p>* Use warm water, mild detergent, and a soft sponge, cloth, or chamois to clean Lumicor</p> <p>* Surface contamination may be cleaned using kerosene, hexane, or aliphatic naphtha, or any acrylic cleaner, such as Novus. Always follow manufacturers recommended use and safety procedures</p> <p>* Remove any oily residue left behind from solvent cleaning with detergent and water</p> <p>Do not use squeegee, scraper, or synthetic rags that may scratch Lumicor</p> <p>When cleaning, never scrub Alta. Gently wipe surface with a soft scratch free cloth.</p> <p><b>REFINISHING</b></p> <p>* Light refinishing - if there is only a light scratch, refinishing can be achieved by using rubbing the area in a random circular motion with a fine steel scouring pad (Scotch-brite). Test in an inconspicuous area before attempting a main area on the job.</p> <p>Heavy refinishing - contact Baresque for details</p>
<b>ENV INFORMATION</b>	Panels are able to be easily recycled. Contact your nearest Baresque branch for details.