Acoustics » Acoustic Panels



Brand: **Zintra**

Applications: Walls



Acoustics » Acoustic Panels



zintraembossed_molecular_s unshine_promo_2.jpg





Acoustics » Acoustic Panels

Zintra Embossed adds a sense of luxury to acoustics and warmth to cold, hard spaces.Molecular brings an abstract pattern in a range of 28 colours.

✓ Absorbs Noise	✓ Bleach Cleanable	\checkmark Environmentally Friendly				
✓ Extended Warranty	✓ Solution Dyed Yarns					
Description	Zintra Embossed adds a luxurious feel to Zintra™s extensive range of acoustic solutions. Ideal for spaces that not only need noise absorption, but also a sumptuous design element only possible through tactile, three-dimensional surfaces. Zintra's heather adds warmth to what can often be cold, hard spaces, while consistent patterns progressively match across sheets so there is a seamless design that's easy to install as either large panels or ceilings tiles. Zintra Embossed Features: * Suitable for wall cladding or ceilings * designed for easy north/south and east/west pattern matching * 108" (2745mm) sheet size allows join-free floor-to-ceiling and easy fitout * Available in 24 colours and 4 wood effects Download the complete Zintra Embossed brochure					
How to Specify	1. Design 2. colour 3. Wall Panel or Ceiling Tile					
Composition	Zintra Acoustic Panel - 100% Solution Dyed (Colour Through) Polyester. 2.3 kg/m²					
Environmental Info	Easily recycled through standard recycling channels					
Finishes	Zintra Panel - Matt. Check out the Zintra 12mm colour range in the DOWNLOADS					
Dimensions	Wall Panels - 2745mm x 1118mm Ceiling Tiles - 594mm x 594mm					
Fire Rating	05 2003 for the purpose of determining the by the Building Code of Australia for the and ceiling linings.					
	Specific Extinction - Less than 250m²,	/kg				
Lead Time	• 2-3 weeks.					
	 Additonal 1-week for Western Austra 	ilia.				
Fabrication Techniques	Stanley knife and straight edge					



Acoustics » Acoustic Panels

Suggested Installation	Walls - adhere to substrate using contact adhesive or Liquid Nails. Ceilings - lay tiles into ceiling grid.		
Care Instructions	Vacuum to remove dust.		
	Dab Zintra with a damp clean cloth and mild solution of liquid detergent and warm water. Repeat using only clean water, then pat dry with a lint free cloth.		
	For difficult stains, use a solution of household bleach (10% bleach / 90% water). To remove the bleach, repeat using a clean, water dampened cloth, then pat dry.		
	Always test in an inconspicuous area first and if you don't see the expected results, contact us.		
Warranty	5-year warranty. Visit baresque.com.au/warranty for complete details.		
Customisable	The Zintra Acoustic Solutions range is customisable to your project. Please get in touch with your local contact for details.		
Additional Comments	r only. Ceiling Tiles available in a set of 8 Zintra Embossed is only suitable for sided applications.		



Acoustics » Acoustic Panels

Colour & Finish Options

BARK/COCOA	BRICK	CADET	CHAMBRAY/ PERIWINKLE	COBALT/NAVY
ECRU/TAUPE	EUCALYPTUS	FOSSIL	FROST/WHITE	GRASS/LIME
GREIGE	IRON BARK	IVORY/MILKY	LINEN/CREAM	MALACHITE
MANDARIN/ORANGE	MERBAU	MIDNIGHT	OCHRE/BLUSH	OLIVE
PEBBLE	PEWTER/GREY	SKY/BLUE	SLATE/ASH	SMOKE/SILVER



1300 306 399 info@baresque.com.au baresque.com.au

Acoustics » Acoustic Panels





SUNSHINE/YELLOW



TAR/BLACK

SPOTTED GUM

1300 306 399 info@baresque.com.au baresque.com.au

