STONE



Brand: **Reatec**

Applications: **Walls, Joinery**

STONE

Reatec Stone reflects traditional Natural marble Stone, offering a new and innovative way to design with Stone that's lightweight with high durability

✓ **Bleach Cleanable**

Description

Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing. Utilising state of the art, multi layer printing and minute embossing, its appearance is almost indistinguishable from real wood or stone. Reatec is stain and solvent/chemical resistant, anti-bacterial, anti-mould, colorfast, washable, scrubbable, and abrasion resistant. A pdf with full Reatec Test Results can be found on the product Downloads tab on the website. Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms. Go to the DOWNLOADS tab for our Reatec Additional Spec Sheet and Installation Guide.

Composition

Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing 350 g/m²

Pattern Repeat Size

N/A

Roll Size

122cm wide x 50m - Available by the lineal metre

Fire Rating

Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.

Classification - Group 1
Specific Extinction - Less than 250m²/kg

Lead Time

• 2-weeks (approx.) from Wednesday, subject to stock availability.

• Additional 1-week for Western Australia.

• Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

Suggested Installation

Reatec is a specialised product and should only be installed by a trained installer.

It is strongly recommended that the installation instructions from our product downloads are read and understood.

As Reatec is a thin film, the substrate should be prepared as smooth as possible to avoid visible unevenness.

Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.

Feel free to contact Baresque with any installation questions.

STONE

Care Instructions	Wipe material with a clean, soft cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then dry with a lint free cloth. Avoid using wax polishes, solvents or concentrated abrasives. For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration. Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.
Warranty	2-year warranty. Visit **baresque.com.au/warranty** for complete details.

STONE

Colour & Finish Options

TC4577


TC4578


TC4579

TC4580

TC4581

TC4584


TC4586


TC4587


TC5207


TC5208


TC5211


TC5212


TC5213


TC5214



TC5553



TC5554

TN5209


TN5210


TN5319


TN5320


TN5321


TN5322


TN5323


TN5324


TN5325

1300 306 399
info@baresque.com.au
baresque.com.au

baresque