KOMOREBI CANOPY

Wallcoverings » Architectural Film



Brand: **Reatec**

Applications: Walls, Joinery



Wallcoverings » Architectural Film

KOMOREBI - CANOPY

anti-mould, colorfast, washable, scrubbable, and abrasion resistant. A pdf with fu Reatec Test Results can be found on the product Downloads tab on the website. Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms. Go to the DOWNLOADS tab for our Reatec Additional Spec Sheet and Installation Guide. Composition Reatec is a durable and realistic architectural film with a pressure sensitive adhesive and air removal system backing 350 g/m² Pattern Repeat Size N/A Roll Size 122cm wide x 50m - Available by the lineal metre Fire Rating Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg Lead Time • 2-weeks (approx.) from Wednesday, subject to stock availability. • Additional 1-week for Western Australia. • Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Installation Reatec is a specialised product and should only be installed by a trained installer installer in ti is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smo	✓ Bleach Cleanable	
adhesive and air removal system backing 350 g/m² Pattern Repeat Size N/A Roll Size 122cm wide x 50m - Available by the lineal metre Fire Rating Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg Lead Time • 2-weeks (approx.) from Wednesday, subject to stock availability. • Additional 1-week for Western Australia. • Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Reatec is a specialised product and should only be installed by a trained installer It is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.	Description	adhesive and air removal system backing. Utilising state of the art, multi layer printing and minute embossing, its appearance is almost indistinguishable from real wood or stone. Reatec is stain and solvent/chemical resistant, anti-bacterial, anti-mould, colorfast, washable, scrubbable, and abrasion resistant. A pdf with full Reatec Test Results can be found on the product Downloads tab on the website. Reatec can be stretched to cover the corners and curves and is suitable for both indoor and outdoor uses including kitchens and bathrooms. Go to the
Roll Size 122cm wide x 50m - Available by the lineal metre Fire Rating Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg Lead Time • 2-weeks (approx.) from Wednesday, subject to stock availability. • Additional 1-week for Western Australia. • Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Reatec is a specialised product and should only be installed by a trained installer lit is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.	Composition	
Fire Rating Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg Lead Time • 2-weeks (approx.) from Wednesday, subject to stock availability. • Additional 1-week for Western Australia. • Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Reatec is a specialised product and should only be installed by a trained installer It is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior applications.	Pattern Repeat Size	N/A
Group Number classification required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings. Classification - Group 1 Specific Extinction - Less than 250m²/kg Lead Time • 2-weeks (approx.) from Wednesday, subject to stock availability. • Additional 1-week for Western Australia. • Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Installation Reatec is a specialised product and should only be installed by a trained installer It is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.	Roll Size	122cm wide x 50m - Available by the lineal metre
 Additional 1-week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for detai and pricing. Suggested Installation Reatec is a specialised product and should only be installed by a trained installer It is strongly recommended that the installation instructions from our product downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications. 	Fire Rating	control of fire spread on interior wall and ceiling linings. Classification - Group 1
InstallationIt is strongly recommended that the installation instructions from our product downloads are read and understood.As Reatec is a thin film, the substrate should be prepared as smooth as possible avoid visible unevenness.Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.	Lead Time	 Additional 1-week for Western Australia. Express delivery is available subject to a surcharge. Contact Baresque for details
		downloads are read and understood. As Reatec is a thin film, the substrate should be prepared as smooth as possible to avoid visible unevenness. Reatec can be installed and repaired on-site, resulting in almost no downtime for both interior and exterior applications.



KOMOREBI CANOPY

Wallcoverings » Architectural Film

Care Instructions	Wipe material with a clean, soft cloth dampened with a mild solution of liquid detergent and warm water. Repeat using only clean water, then dry with a lint free cloth.
	Avoid using wax polishes, solvents or concentrated abrasives.
	For more difficult stains, dampen a soft white cloth with a solution of household bleach (10% bleach / 90% water). Rub gently. Rinse with a water dampened cloth to remove bleach concentration.
	Always test in an inconspicuous area first. If care instructions don't deliver the expected results, cease cleaning method immediately and contact Baresque for assistance.
Warranty	2-year warranty. Visit baresque.com.au/warranty for complete details.



KOMOREBI CANOPY

Wallcoverings » Architectural Film

Colour & Finish Options





TX5216

TX5307

