

HEAT SHIELDING SHADOW

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS Heat Shielding Shadow reduces solar heat gain while maintaining clear visibility and providing UV protection to improve energy efficiency and interior comfort.

Description

CLEAS Heat Shielding Shadow is designed to improve interior comfort by reducing solar heat gain while preserving clear visibility through glass. It also provides UV protection to help minimise fading of furnishings and interior finishes, making it ideal for spaces exposed to strong sunlight.

Manufactured using high-transparency polyester film, it delivers excellent optical clarity for a clear external view, while also helping to block up to 97% of infrared heat for enhanced thermal performance. Suitable for residential, commercial and hospitality applications, it offers a durable and effective solution for improving the performance of glazed surfaces.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths:

GF1113 SHADOW 40 and GF1114 SHADOW 20: 97cm and 125cm

GF1410 STEAM SHADOW 20: 125cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

HEAT SHIELDING SHADOW

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.

Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.

HEAT SHIELDING SHADOW

Wallcoverings » Architectural Film


Colour & Finish Options



GF1113 SHADOW 40



GF1114 SHADOW 20



GF1410 STEAM
SHADOW 20