

ECORIM 70

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS Ecorim 70 improves energy efficiency and interior comfort by reducing heat transfer, limiting solar radiation, maintaining visibility and protecting interiors from UV damage.

Description

CLEAS Ecorim 70 is designed to improve interior comfort and energy efficiency by reducing heat transfer and limiting the impact of solar radiation through glass surfaces. It helps maintain clear visibility while providing UV protection to support the preservation of interior furnishings and finishes.

Manufactured using high-transparency polyester film, it delivers excellent optical clarity for a clear external view while helping to block up to 97% of infrared heat for enhanced thermal performance. Suitable for residential, commercial and hospitality applications, it provides a durable and effective solution for improving the performance of glazed surfaces.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths: 127cm and 152.4cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

ECORIM 70

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.

Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.

ECORIM 70

Wallcoverings » Architectural Film

Colour & Finish Options



GF1206