

LUCENT 90

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS Lucent 90 is a high-transparency heat-shielding film that reduces solar heat gain, improves energy efficiency, allows natural light flow and provides UV protection to help preserve interiors.

Description

CLEAS Lucent 90 is a high-transparency solar control film designed to improve interior comfort while preserving maximum natural light and clear visibility. Its low-radiation performance helps reduce solar heat gain and improve energy efficiency, while UV protection assists in protecting interior furnishings and finishes from fading and damage.

Manufactured using high-transparency polyester film, it delivers excellent optical clarity for a clear external view while helping to block up to 97% of infrared heat. Suitable for residential, commercial and hospitality applications, it provides a durable and effective solution for enhancing the performance of glazed surfaces.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths: 97cm, 125cm and 155cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

LUCENT 90

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.


Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.

LUCENT 90

Wallcoverings » Architectural Film

Colour & Finish Options



GF1101