

SHATTER RESISTANT KIND

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS Shatter Resistant Kind holds glass fragments together upon impact, reducing the risk of injury and damage, maintaining clear visibility while reinforcing glass strength.

Description

CLEAS Shatter Resistant Kind films provide enhanced safety and protection by helping to hold glass fragments together upon impact, reducing the risk of injury and damage while maintaining clear visibility. Designed to reinforce existing glazing, the high-performance film helps improve glass strength without compromising natural light or external views.

Manufactured using high-transparency polyester film, it offers superior optical clarity while helping to block up to 97% of infrared heat for improved interior comfort. Suitable for residential, commercial and hospitality applications, CLEAS Shatter Resistant films deliver a reliable and discreet solution for improving glass safety and performance.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths: 96cm, 127cm and 152.4cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

SHATTER RESISTANT KIND

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.


Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.

SHATTER RESISTANT KIND

Wallcoverings » Architectural Film

Colour & Finish Options



GF1452 KIND 90