

LOW REFLECTION

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS Low Reflection is a high-performance glass film that offers low reflectivity and high transparency, minimizing glare while maintaining natural light.

Description

CLEAS Low Reflection is designed to minimise unwanted glass reflections and glare while maintaining exceptional transparency for clearer, more comfortable viewing. Providing low reflectivity without compromising natural light, it enhances visibility through glass surfaces, making it ideal for display cases, museums, retail environments and spaces with scenic views.

Manufactured using high-transparency polyester film, it delivers excellent optical clarity for a clear external view while helping to block up to 97% of infrared heat for improved interior comfort. Suitable for residential, commercial and hospitality applications, CLEAS Low Reflection offers a durable and practical solution for enhancing the performance and visual clarity of glazed surfaces.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths: 122cm and 150cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

LOW REFLECTION

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.


Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.


LOW REFLECTION

Wallcoverings » Architectural Film

Colour & Finish Options



GF1401 LUCLEAR II



GF1402 LUCLEAR II EX