

UV PROTECTION AND HEAT REJECTION

Wallcoverings » Architectural Film

Brand: **Sangetsu**

Collections: **Glass Film**

Applications: **Glass**

CLEAS UV Protection and Heat Rejection is a high-performance glass film designed to block harmful UV rays and reduce heat transfer while maintaining excellent transparency and improving interior comfort.

Description

CLEAS UV Protection and Heat Rejection Film provides an effective solution for improving the performance of existing glazing while maintaining a clear and natural view through glass surfaces. Designed to reduce solar heat gain and minimise the impact of UV exposure, it helps create more comfortable interior environments while protecting furnishings and finishes from sun damage.

Manufactured using high-transparency polyester film, it delivers excellent optical clarity while helping to block up to 97% of infrared heat for improved interior comfort. Suitable for residential, commercial and hospitality applications, CLEAS UV Protection and Heat Rejection Film offers a durable and discreet solution for enhancing the efficiency and functionality of windows, doors and glazed surfaces.

Composition

High-clarity polyester (PET) film with functional coating, and durable scratch-resistant finish

Pattern Repeat Size

Various. See Glass Film Product Specification Download for details

Roll Size

Various. See Glass Film Product Specification Download for details.

Dimensions

Available Widths: 97cm, 125cm and 155cm

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

UV PROTECTION AND HEAT REJECTION

Wallcoverings » Architectural Film

Care Instructions

Clean using a soft cloth or rubber squeegee with clean, warm water.

For more persistent soiling, use a mild neutral detergent diluted to 1–2% with water. Gently wipe the surface in a single direction, then rinse thoroughly with clean water to remove any residue.

Do not scrub back and forth, as this may damage the surface.

Do not dry-wipe, as this may cause fine scratches.

Avoid leaving dirt or debris on the surface, as this may accelerate wear. Regular cleaning is recommended to maintain appearance and performance.

Do not use ammonia-based cleaners, chlorine-based cleaners, organic solvents, or abrasive cleaning agents.

Do not apply stickers, tape, or labels to the surface, and avoid writing on the material. Prevent any actions that may scratch or damage the film.


Warranty

2-year warranty. Visit baresque.com.au/warranty for complete details.

UV PROTECTION AND HEAT REJECTION

Wallcoverings » Architectural Film

Colour & Finish Options



GF1462