SOUTH BEACH SILK

Brand: **P3tec**

Applications: **Walls**

1300 306 399
info@baresque.com.au
baresque.com.au

baresque

SOUTH BEACH SILK

SOUTH BEACH SILK

South Beach collection's sandy neutrals, subtle textures, & silky touch bring timeless sophistication and summer vibes indoors.

- ✓ **Bleach Cleanable**
- ✓ **Easy Clean**
- ✓ **Extended Warranty**
- ✓ **Extreme Durability**
- ✓ **High Stain Resistance**
- ✓ **Ultra Performance**

Description

South Beach Silk embodies the luxurious and youthful energy of Miami's South Beach. With its predominantly sandy neutral palette, delicate colour variations, and airy texture, this collection captures the breezy summer spirit while maintaining a sense of sophistication and timeless appeal.

South Beach Silk aims to bring a touch of this local decor inspiration to a broader audience, allowing people to infuse their spaces with the soul of South Beach and the allure of silk.

Composition

Extra thick vinyl face on a heavy polyester / cotton knit fabric backing.

Environmental Info

Formaldehyde free

Heavy metals free

Perfluorooctanoic acid free

No solvent inks

Low VOC emissions. Any VOCs dissipate quickly (faster than paint) through normal ventilation and have no recognised adverse impact on indoor air quality.

Durability means products do not need to be replaced regularly due to wear and tear and being cleanable, vinyl products are ideal for helping keep commercial environments clean of bacteria.

Baresque will only deal with vinyl manufacturers that comply with applicable state and federal regulations, provide a factory that is safe and clean for its employees to work in, recycle scrap and inks during the manufacturing process to minimize waste related to production.

Pattern Repeat Size

Not Applicable

Roll Size

137cm (trims to 122cm wide) x 13.7m - Available by the full roll only

Abrasion

ASTM D -5420-10 Gardner Method

SOUTH BEACH SILK

Fire Rating

Tested in accordance with AS ISO 9705 2003 for the purpose of determining the Group Number classification as required by the Building Code of Australia for the control of fire spread on interior wall and ceiling linings.

The result achieved was:
Classification - Group 2
Specific Extinction - Less than 250m²/kg

Lead Time

- 2-weeks (approx.) from Wednesday, subject to stock availability.
- Additional 1-week for Western Australia.
- Express delivery is available subject to a surcharge. Contact Baresque for details and pricing.

Suggested Installation

Reverse hang alternate drops/overlap and double cut.

Advanced Wall Protection requires a specific installation method and we strongly recommend you use one of our recommended installers.

Download the Installation Instructions for details.

Baresque recommends and supply Roman brand adhesives and primers.

Care Instructions

1. Completion:

Immediately upon completion of installation, installer shall make sure that these products are cleaned and free of any layout marks, excess adhesive or surface blemishes. Remove excess adhesive with methods and materials recommended by the adhesive manufacturer.

2. Clean-Up and Routine Maintenance:

Rigid Profiles: For general cleaning, use disinfectant cleaner.

All Purpose Cleaner Heavy Duty: Use a clean, lint-free cloth and wipe clean. Do not use any abrasive cleaning cloths or sponges.

1. Spray products onto profile and wipe with a dampened cloth.

2. Repeat process if stain remains. If cleaning product residue remains, rinse with water.

Warranty

5-year warranty. Visit **baresque.com.au/warranty** for complete details.

SOUTH BEACH SILK

Colour & Finish Options


P3T-60425 TOUCH OF TAN


P3T-60426 CASHMERE

P3T-60427 CREAM

P3T-60428 BABY'S BREATH

P3T-60429 PERFECT WHITE

P3T-60430 BONE


P3T-60431 MOONSTRUCK

P3T-60432 GREY PEARL


P3T-60433 GENTLE GREY


P3T-60434 CLAM UP

P3T-60435 MIDNIGHT


P3T-60436 CARBON DATING


P3T-60437 STONE MASON

P3T-60438 GARDENIA


P3T-60439 BEACH GLASS

1300 306 399
info@baresque.com.au
baresque.com.au

baresque